

## CHARGERS

5 YEAR WARRANTY

## Smart &amp; Quick charger – BQ CC55

- Rapid charge
- Individual management/charge control (“Smart Charge<sup>(1)</sup>”)
- Can be used all over the world (100-240 V)
- Case color: white



Item	Specifications
Input	AC100-240V 50-60Hz
Input part Structure	Fixed plug
Charging control	Smart Charge <sup>1</sup> / -ΔV / Timer
Indicator	LED x 4 Charging: ON, Fully charged: OFF
Charger battery	AA x 1, 2, 3, 4 / AAA x 1, 2, 3, 4 cells
Charging time <sup>(2)</sup>	AA: Approx 1.5 hours / 3 hours [2,000 mAh] AAA: Approx 1.5 hours / 3 hours [800 mAh]
Charger size (W x H x D)	68 x 120 x 65.5 mm (EU) / 68 x 120 x 62 mm (UK)
Weight	with EU-plug: 124 g - with UK-plug: 131 g

<sup>(1)</sup> This charger has “Smart Charge” function which checks voltage and temperature of battery automatically. Thanks to Smart Charge function, it saves time of charging and loss of energy & money.

## PRODUCT BENEFITS

- Improved consumer communication, designed to aid product rotation
- Clear time indications and features
- Free 5 year warranty for added reassurance
- All chargers have lead-free soldering, less harmful for the environment
- Worldwide compatibility
- Safety: non rechargeable detection
- LED Timer ready indication
- For all Ni-MH batteries

## Compact charger – BQ CC50

- Can charge AA / AAA 2 cells
- Can be used all over the world (100-240 V)
- Safety timer: max. 13h
- Case color: white

Item	Specifications
Input	AC 100-240 V 50-60 Hz
Input part Structure	Fixed plug
Charging control	Timer cut (13 hours) Individual
Indicator	LED x 2 Charging: ON, Fully charged: OFF
Charger battery	AA x 1, 2 / AAA x 1, 2 cells
Charging time <sup>(2)</sup>	AA: Approx 10h [2,000 mAh]; AAA: Approx 10h [800 mAh]
Charger size (W x H x D)	50 x 121 x 66.2 mm (EU) / 50 x 121 x 61.2 mm (UK)
Weight	with EU-plug: 86 g - with UK-plug: 96 g



## Advanced charger – BQ CC17

- Can charge AA / AAA 4 cells
- Can be used all over the world (100-240 V)
- Individual management/-ΔV Control
- Case color: white



Item	Specifications
Input	AC 100-240 V 50-60 Hz
Input part Structure	Fixed plug
Charging control	-ΔV /Timer
Indicator	LED x 4 Charging: ON, Fully charged: OFF
Charger battery	AA x 1, 2, 3, 4 / AAA x 1, 2, 3, 4 cells
Charging time <sup>(2)</sup>	AA: Approx 7h [2,000 mAh]; AAA: Approx 6h [800 mAh]
Charger size (W x H x D)	65 x 105 x 65 mm
Weight	107 g

## Universal charger – BQ CC15

- Can charge AA / AAA / C / D 1-4 cells
- Can charge 9V 1-2 cells
- Can be used all over the world (100-240 V)
- Automatic switch-off when charged (-ΔV)
- Case color: white

Item	Specifications
Input	AC 100-240 V 50-60 Hz
Input part Structure	AC cable
Charging control	-ΔV /Timer (excl. 9V battery)
Indicator	LED x 2 Charging: ON, Fully charged: OFF
Charger battery	AA x 1-4 / AAA x 1-4 / C x 1-4 / D x 1-4 / 9V x 1-2 cells
Charging time <sup>(2)</sup>	AA: Approx 6h [2,000 mAh]; AAA: Approx 6h [800 mAh]
Charger size (W x H x D)	110 x 200 x 55 mm
Weight	with EU-plug: 489 g - with UK-plug: 499 g



## Basic charger – BQ CC51

- Can charge AA / AAA 2 or 4 cells
- Can be used all over the world (100-240 V)
- Timer control
- Case color: white



Item	Specifications
Input	AC 100-240 V 50-60 Hz
Input part Structure	Fixed plug
Charging control	Timer cut (13 hours)
Indicator	LED x 2 Charging: ON, Fully charged: OFF
Charger battery	AA x 2, 4 / AAA x 2, 4 cells
Charging time <sup>(2)</sup>	AA: Approx 10h [2,000 mAh]; AAA: Approx 10h [800 mAh]
Charger size (W x H x D)	66 x 108 x 65.1 mm (EU) / 66 x 108 x 62 mm (UK)
Weight	with EU-plug: 100 g - with UK-plug: 110 g

(2) AA/AAA 4 cells.

## Specifications:

Charger	Re-order N° (Kit)	CSU EAN	Batteries included in kit	Blister size (mm) (W x H x D)	Blisters/ Carton
BQ-CC55	K-KJ55MGD40E	5410853057789	4x P6 1900	105 x 200 x 72	8
BQ-CC55	K-KJ55MGD40U	5410853057802	4x P6 1900	105 x 200 x 72	8
BQ-CC17	K-KJ17MGD40E	5410853057796	4x P6 1900	105 x 200 x 72	8
BQ-CC51	K-KJ51MGD42E	5410853056973	4x P6 1900 / 2x P03 750	105 x 200 x 72	8
BQ-CC51	K-KJ51MGD40U	5410853057819	4x P6 1900	105 x 200 x 72	8
BQ-CC50	K-KJ50LGA20E	5410853056966	2x P6 1900	105 x 200 x 72	8
BQ-CC15	BQ-CC15E	5025232672141	-	167 x 342 x 67	8

(3) AA/AAA 2 cells.