

## eneloop lite \*\*

## Ideal for devices requiring low-to-medium power

eneloop lite batteries are ideal for devices requiring low-to-medium power, such as DECT phones and remote controls.


They can be recharged up to 3000 times<sup>(1)</sup> which makes it even more economically and environment-friendly.






Panasonic internal IEC 61951-2 2011 (7.5.1.3) testing; 1000 times according to Panasonic internal IEC 61951-2 2017 (7.5.1.4) testing











## eneloop lite \*\*



After **5** years capacity remains

Our packagings are FSC® certified



The mark of responsible forestry









Item code	Size	Min. Capacity	Global Code	CSU EAN	Batteries/ CSU	CSU/ Carton	
30010016	AAA	550 mAh	BK-4LCCE/2CP	5410853064336	2	20	
30010017	AAA	000	BK-4LCCE/2CP DECT	011000000000	2	20	
30010010	AAA	550 mAh	BK-4LCCE/4CP	5410853064350	4	20	

eneloop lite

(i) Panasonic internal IEC 61951-2(7.3.2) testing – varies according to conditions of use.
(ii) Panasonic internal IEC 61951-2 2011(7.5.1.3) testing; 1000 times according to Panasonic internal IEC 61951-2 2017(7.5.1.4) testing.
(iii) Battery tested at 20°C ambient temperature self-discharge condition 0.2lt (E.V.=1.0V).

